

ALEDIN 2

The Aledin 2 is the new successor for the undefeated proprietary Aledin 1 which was developed in 2009/10 by Brother, Brother & Sons for the Robert Juliat 600 series zoom profile spots. You can upgrade your tungsten Juliat profile to LED in two minutes.



Powersaving - Long lamp life - Reliability - Smooth dimming

SPECIFICATIONS

POWER:

Switchmode power supply
AC Power: 100 – 240 V nominal, 50/60 Hz
Max. power consumption: 115 W.
Standby power: 5 W.
1 Amp @ 110V / 0,5 Amp @ 240V
Powercon IN and OUT for daisy chaining
Ambient operating temperature: 0-40°C / 0-104°F
Ultra silent pulse fan assisting the large heatsink when needed.

LAMP:

High quality Cold Led array 5600 Kelvin. CRI min. 72,
with 70% Lumen maintenance over 50.000 hours.
High quality Cold Led array 3200 Kelvin. CRI min. 80,
with 70% Lumen maintenance over 50.000 hours

CONTROL:

DMX512
8/16bit dimming 0-100%
1 or 3 control channels at 8bit / 2 or 4 channels at 16bit
Digital display
Ultra fast strobe channels



Weight: 15,41 kg / 33,95 lbs

Example when mounted in 614 SX profile



In compliance with the RoHS and WEEE directives.

In compliance with EMC standards: EN 55103-1 & EN 55103-2: EN 55022, EN 55103-1 Annex A, EN 55022, EN 61000-3-2, EN 61000-3-3, EN 55103-1, EN 61000-4-2, EN 61000-4-3, EN 61000-4-4, EN 61000-4-5, EN 61000-4-6, EN 55103-1 Annex B, EN 55103-1 Annex A, EN 61000-4-11

TEL.: +45 70 27 42 41 - MAIL: BROTHERS@BROTHERS-SONS.DK
WWW.BROTHERS-SONS.DK

BROTHER, BROTHER & SONS Aps

